



Office: B-20, Parmanu Nagar, Sector -IV,
Vashi, Navi Mumbai - 400 703. Works: MIDC, Turbhe
Tel.:(022) 2782 1641/48 • Fax : (022) 27821124
Web : www.ssfilters.com • email: info@ssfilters.com

SS FILTERS PVT. LTD.

AN ISO 9001:2008 COMPANY

Specification Sheet

SS pleated filter cartridge



SS Pleated filter cartridges are the perfect choice for high temperature (250°C & above) & high viscosity applications. MOC is SS 304 or SS 316 or SS 316L. They offer excellent reliability for critical applications and have high dirt holding capacity. The cartridges are designed for cleanable and reusable applications so as to eliminate frequent cartridge change out.

FEATURES & BENEFITS

- 100% Stainless steel
- Superior chemical compatibility
- Excellent mechanical strength
- High Thermal tolerance
- High dirt holding capacity

PRODUCT SPECIFICATIONS

Micron Rating	1, 5, 10, 20, 40 μ
MOC	SS316L / SS 316/ SS 304
Core, End cap, support cage	SS316L / SS 316/ SS304
Length	10" , 20" , 30" , 40"
Inner dia	Approx 28mm or customer specification
Outer dia	63mm, 70mm, 80mm
O-ring material	EPDM ,Buna-N, Silicone, Viton
Effective Surface area	7.5 Sq. feet (0.65sqm) per 10" cartridge element
Max. Operating Temperature	Up to 250 °C
Sterilization	
Autoclave	121°C, 30min
Hot water	80C°, 30min

CONSTRUCTION:

- Filter media: SS 316L
- End Caps: SS 316/ SS 316L
- 'O' Ring/ Gaskets: Silicone/ EPDM/ Viton

CONFIGURATION:

- Double open end- DOE
- Code 7S (226- double 'O' Ring / fin)
- 1" BSP threaded, other end closed

APPLICATIONS:

- Corrosive gas & liquid filtration
- Steam filtration
- Beverage industry
- Solid catalyst recovery
- Filtration of slurry oil
- Filtration of petrochemical products
- High temperature gas filtration
- Vent applications
- Chemical reagents
- Fluidization
- Sparging
- Highly viscous fluids